

"ULTRA24" — BASIC

CHROMIUM

SUPLHATE

THE CHROME IS REDUCED WITH MOSLASSES.

PHYSICAL APPERIANCE:

ROTARY STEAM DRUM DRIED MATERIAL FREE FLOWING POWDER GREEN IN COLOUR HIGHLY SOLUBLE IN COLD WATER

ANALYTICAL DATA

CHROMIUM OXIDE AS Cr2 O3

BASICITY

33 - 35% Min

FREE SULPHATES AS NA2SO4

PH OF AQUEOUS SOLUTION

MOISTURE, PRECENT BY MASS

EXCESS MOLASSES

24% +/- 1.00.

30 - 33% Min

2.9-3.00

10% MAX

NIL

USAGE: "**ULTRA24"** BASIC CHROMIUM SULPHATE IS USED FOR CHROME

TANNING OF ALL TYPES OF HIDES/SKINS. ALSO USED IN DYEING

OF MINERAL KHAKI CLOTH AND ACID DYES.

PACKING: 50 KGS HDPE BAGS WITH POLYTHENE LINER.

STORAGE: TO BE STORED IN A DRY PLACE. SOLUBILITY DETERIORATES

WHEN STORED IN HOT CONDITIONS.

SAFETY PRECAUTIONS:

INHALE: REMOVE TO FRESH AIR SUPPORT BREATHING EYES: RINSE IMMEDIATELY WITH PLENTY OF WATER

SKIN: TAKE OFF IMMEDIATELY ALL CONTAMINATED CLOTHS AND WASH

WITH PLENTY OF SOAP WATER.

In view of the wide variety of uses and procedures we cannot assume any responsibility for the results obtained. Our recommendations are based on very careful tests for your quidance.

ULTRA CHEMICAL WORKS

209 Anantdeep Chambers, 273/277 Narshi Natha Street, Mumbai: 400 009. (India) Ph: +91 22 66359695 Fax: +91 22 66359694 E-mail: info@ultrachem.co.in Website: www.ultrachem.co.in



ULTRA CHEMICAL WORKS

209 Anantdeep Chambers, 273/277 Narshi Natha Street, Mumbai: 400 009. (India) Ph: +91 22 66359695 Fax: +91 22 66359694 E-mail: info@ultrachem.co.in Website: www.ultrachem.co.in